

NAVSHIPREPFAC YOKOSUKA  
LOCAL STANDARD ITEM

FY-02

ITEM NO: 099-84YO  
DATE: 01 JUL 1998  
CATEGORY: I

1. SCOPE:

1.1 Title: Accountability of Temporary Fasteners; provide

2. REFERENCES:

a. None.

3. REQUIREMENTS:

3.1 Submit four legible copies of a report upon installation of any temporary fasteners to NAVSHIPREPFAC. The report is due one working day after start of installation and shall contain the following information:

3.1.1 System.

3.1.2 Component (valves, flanges, foundations, brackets).

3.1.3 Location (deck, frame, port, starboard, tank, manhole).

3.2 Paint temporary fasteners blaze orange.

3.3 Maintain a log/file of installed/removed temporary fasteners with the information described in 3.1.

3.4 Remove temporary fasteners prior to any testing, lagging, and/or painting of systems or components.

3.4.1 Submit four legible copies of a report to NAVSHIPREPFAC stating that temporary fasteners have been removed.

4. NOTES:

4.1 For purposes of this item, temporary fasteners are defined as those fasteners that are installed in lieu of the final fasteners that are specified for system installation. Examples would include temporary fasteners used to hold fittings, valves, or machinery in place.